


**Size Range : 2" to 24" Flanged**

"Suzhik" Multi function Pneumatic Drum Type Control Valve can be used as isolating valve and also for flow controlling application. Special Design Namur style Ball Valve mounted on main valve, couple with Pneumatic Actuator for operation. Its simple Technique and heavy duty design impact a unique stands against other Control valve. High Flow factor and simple Pilot Control makes its very user friendly.



**Features :**

- ▶ Exclusive smart design for Big size & cross country Water line Projects.
- ▶ High Cv Value, with Low Pressure Hammering
- ▶ Choice of operating Control available in Pneumatic Actuator like On Off / Modulating / On-Off with Feedback
- ▶ On-Off & Proportionate (Modulating) control having Input Single of 4~20mA available in Pneumatic Actuator
- ▶ Precise Pressure control and repeatability can be achieved for Proportionate Control Application.



**Dimensions :** (All Dimensions are in mm)

Valve Model	Valve Size		L	Weight Approx	CV
	MM	Inch			
DNF - 50	2"	50	190	12	75
DNF - 65	2½"	65	210	15	105
DNF - 80	3"	80	225	18	140
DNF - 100	4"	100	250	24	260
DNF - 125	5"	125	280	32	390
DNF - 150	6"	150	310	44	550
DNF - 200	8"	200	420	87	1000
DNF - 250	10"	250	470	152	1600
DNF - 300	12"	300	530	202	2200
DNF - 350	14"	350	600	285	3000
DNF - 400	16"	400	600	—	4000
DNF - 450	18"	450	750	—	5300
DNF - 500	20"	500	750	—	6100
DNF - 600	24"	600	900	—	9200