

THB QUICK COUPLER

MATERIAL : STEEL

20SHA	5/16" (HOSE)			20PHA	5/16" (HOSE)
30SHA	3/8"(HOSE)			30PHA	3/8"(HOSE)
40SHA	1/2"(HOSE)			40PHA	1/2"(HOSE)
20SFA	1/4"(PT)			20PFA	1/4"(PT)
30SFA	3/8"(PT)			30PFA	3/8"(PT)
40SFA	1/2"(PT)			40PFA	1/2"(PT)
20SMA	1/4"(PT)			20PMA	1/4"(PT)
30SMA	3/8"(PT)			30PMA	3/8"(PT)
40SMA	1/2"(PT)			40PMA	1/2"(PT)
20SPA	5×8MM			20PPA	5×8MM
30SPA	6.5×10MM			30PPA	6.5×10MM
40SPA	8×12MM			40PPA	8×12MM

THB HIGH FLOW QUICK COUPLERS / STEEL

400 SMA	1/2"PT			400 PHA	1/2" HOSE
600 SMA	3/4"PT			600 PHA	3/4" HOSE
800 SMA	1"PT			800 PHA	1" HOSE

THB MULTI COUPLERS



SMV



SMY



SML



SMT



SMX

ONE TOUCH COUPLERS

20SHT	5/16"(HOSE)	
30SHT	3/8"(HOSE)	
40SHT	1/2"(HOSE)	
20SFT	1/4"(PT)	
30SFT	3/8"(PT)	
40SFT	1/2"(PT)	
20SMT	1/4"(PT)	
30SMT	3/8"(PT)	
40SMT	1/2"(PT)	
20SPT	5X8MM	
30SPT	6.5X10MM	
40SPT	8X12MM	

APPLICATIONS

- * Pneumatic tools,
- * Air piping
- * Air pressure equipment
- * Water piping

FEATURES

- * One-way automatic shut-off value in the socket.
- * Wide variety provides best choice according to application.
- * Hardened important parts are extremely wear resistant and durable.
- * Chrome plated steel body for anti - corrosion, gives long erm, stable functioning.
- * Tested 100,000 times, coupler connection is accurate and reliable.

SPECIFICATION

MATERIAL	BODY:Aluminum
WORKING PRESSURE	10~15 kgf/cm ²
MAXIMUM PRESSURE	15~20 kgf/cm ²
TEMP. RANGE	-20°C~+80°C
SIZE	1/4" (20 type)
SIZE	1/4" (20 type) 3/8" (30 type) 1/2" (40 type)